

Hydraulic Busbar Punchers



HHM-70

Characteristics:

- Strong durable construction.
- Single acting, spring return.
- Quick set up punches & dies system.
- Flat and clean hole edge.
- Punch dies made of high strength steel.
- Carrying handle for easy transportation to the job site.
- Large flat base for added stability.
- Supplied with R2 3/8 male coupler and dust cap.
- Operated by hydraulic pump with rated pressure 700 bar.

Model	Output force (ton)	Punch dies	Max.thickness(mm)		Throat depth (mm)	G.W. (kg)	Packing size (cm)
			mild steel	copper/aluminum busbar			
HHM-70	35	3/8" (11.1mm), 1/2" (14.3mm) 5/8" (17mm), 3/4" (20.6mm)	8	12	110	37.4	33×20×39



HHM-80

Characteristics:

- Strong durable construction.
- Double acting, hydraulic return.
- Quick set up punches & dies system.
- Flat and clean hole edge.
- Punch dies made of high strength steel.
- Top eye bolt for easy handling on the job site.
- Large flat base for added stability.
- Supplied with R2 3/8 male coupler and dust cap.
- Operated by double-acting hydraulic pump with rated pressure 700 bar.

Model	Output force (ton)	Punch dies	Max.thickness(mm)		Throat depth (mm)	G.W. (kg)	Packing size (mm)
			mild steel	copper/aluminum busbar			
HHM-80	50	16mm, 18mm 22mm, 25mm	14	16	115	52.5	370×220×380